

Delta-Q battery chargers are durable and efficient, built for reliability, and charging performance. Each Delta-Q charger has customized cabling and charge profiles for the best application fit and helps improve battery life and performance.

Lead-Acid (Wet / AGM / Gel) & Lithium-ion Options

QuiQ Series

- Identical mechanical design for easy replacement with other QuiQ chargers
- Multicolor LED indicator for charging status and fault/error codes
 - Remote LED indicators are available upon request
- Onboard application with connections and interlock
- Field programmable with up to 10 charging profiles
- Integrated charge cycle and event tracking
 - Download data using QuiQ Programmer (available upon request)



IC650 Series

- High reliability and high efficiency for electricity savings and shorter charge times
- OEM customizable, field replaceable cable design
- Multicolor LED indicator for AC source, battery status, charging, error, fault
- Simple LED display for charge profile, alarm/fault codes
- Field programmable with up to 25 charging profiles
- Auto-recharge for low voltage in maintenance mode
- Integrated charge cycle tracking
 - USB host port for data download and software upgrades
- Optional CAN bus communication
- Optional carrying handle



RC Series

- CANopen and J1939 CAN bus features
- Safety interlock feature for protection while charging
- OEM customizable, field replaceable cable design
- Auto-recharge for low voltage in maintenance mode
- On- or offboard installations
- Over 200 algorithms available
- Optional battery temperature sensing and remote LED
- Optional tricolor LED indicator for battery status, charging, error and fault



Lithium-ion Only Option

ICL Series

- Lithium-specific design to optimally charge lithium batteries (e.g., LCO, NCA, NMC, LMO, LFP, LTO)
- CANopen and J1939 CAN bus features
- Charge cycle data logging for insight into usage and troubleshooting



FSIP's Full New Delta-Q Products Offerings

Model	DC Output Voltage Range	DC Output Current Range	DC Output Power Range	AC Input Voltage Range
QuiQ Series				Dim.: 10.9" x 9.7" x 4.3" Wt.: 11 lbs.
QuiQ 1000	24-72 V	12-25 A	695-1000 W	85-265 VAC
QuiQ 1500	48-72 V	17-30 A	1200-1500 W	108-265 VAC
IC Series				Dim.: 9.9 x 7.3 x 3.1" Wt.: 6.5 lbs.
IC650	24-48 V	13.5-27.1 A	650 W	85-270 VAC
IC900	24-48 V	20-37.5 A	900-960 W	120-240 VAC
IC1200	24-48 V	25-50 A	1200 W	85-270 VAC
RC Series				Dim.: 11.8 x 7.0 x 3.2" Wt.: 8 lbs.
RC900	36-48 V	20-25 A	900 W	85-270 VAC
RC1000	24 V	41.3 A	1000 W	85-270 VAC
RC1200	36-48 V	25-33 A	1200 W	85-270 VAC
ICL Series				Dim.: 11.8 x 7.0 x 3.2" Wt.: 8 lbs.
ICL900	57 V	27 A	900 W	85-270 VAC
ICL1200	57-120 V	15-33.3 A	1200 W	85-270 VAC
ICL1500	58-120 V	18.7-33.3 A	1500 W	85-270 VAC

Remanufactured

FSIP serves as a preferred service center for Delta-Q. This allows us to remanufacture many models and restore each charger to "like-new" conditions. Our remanufactured Delta-Q products are analyzed by certified electronic technicians. All products are also rigorously quality tested.

Current Remanufactured Offerings

- QuiQ Series
- IC Series
- ICL Series
- RC Series

Obsolete Chargers (no longer available new)

- SC Series
- PowerWise QE



Remanufacture & Return (R&R)
Send your unit in to be evaluated, remanufactured, and returned to you with FSIP Remanufacturing warranty.



Rebuilt Exchange (RX)
Purchase a remanufactured unit and remit your rebuildable core to FSIP for credit.



Rebuilt Outright (RO)
Purchase an in-stock remanufactured unit without trading in a rebuildable unit (core).