

FSIP's
exclusive
GREEN

Series is high-frequency, fully automatic, industrial battery chargers for use with either lead-acid or lithium batteries. These units are enclosed in a steel case that may be wall-mounted or mounted onto our optional vertical charging stand. Ideal for light to heavy-duty electric vehicle charging. Available in single or three-phase models.

Features/Benefits

- High energy efficiency rating of greater than 90%
- Charge cycles begin as low as 2 volts
- Soft start charging cycle
- Fast/opportunity charge capable
- Available in 24–80 volts (72 or 96 volt available upon request)
- Suitable for flooded, AGM, gel traction, or lithium batteries
- 7-preloaded charging curves (specialized charging curves available)
- Standard CC/CV/Stop profile (CAN Bus option for lithium batteries)
- Includes 10-foot DC cable
- UL, cUL, and CEC certified
- Remanufacturable



These **GREEN8** units are durable, dependable modular designed for uninterrupted charging. These units are easy to service and repair, when necessary, with little to no downtime.



Photo is of a **GREEN6**, the **GREEN8** will have 4 modules.




NEW bright green LED charging status bar to provide better visibility from further distance
 Multivoltage/multicurrent configurable via front display or USB A/B port
 Charging status indicator
 Easy to read LCD display



Optional Add On:
 Battery Identifier (**BID**)

Optional Add On:
 Integrated Data Logger with Real-Time Clock (**RTC**)



Also comes with rubber feet to stand alone or can be wall-mounted or stand-mounted (with optional **Vertical Charger Stand**)

Model	DC Output Voltage	DC Output Current	Flooded 8-Hour Ah Range (C6)	Flooded 4-Hour Ah Range (C6)	AC Input Breaker	Input Voltage
GREEN8						Dim.: 19.5" x 8.6" x 26.2" Wt.: 95.5 lbs.
24-GREEN8220-24200	24 V	200 A	1,650 Ah	850 Ah	50 A	208-240 VAC
24-GREEN8220-36200	36 V	200 A	1,650 Ah	850 Ah	50 A	208-240 VAC
24-GREEN8220-48200	48 V	200 A	1,650 Ah	850 Ah	50 A	208-240 VAC
24-GREEN8480-24200	24 V	200 A	1,650 Ah	850 Ah	25 A	480 VAC
24-GREEN8480-36200	36 V	200 A	1,650 Ah	850 Ah	25 A	480 VAC
24-GREEN8480-48200	48 V	200 A	1,650 Ah	850 Ah	25 A	480 VAC
24-GREEN8480-80130	80 V	130 A	1,100 Ah	575 Ah	25 A	480 VAC