



EV100 CONTACTORS

Application

EV100 contactors are designed for use in DC applications, with battery or rectified power. They perform power switching functions for traction drives as well as pump motor and other electric vehicle power switching operations. The contactors have been successfully applied to meet Underwriter's Laboratories. They are listed under U/L file number AU2422.

Specifications

100 Amp Contactors

Rating / Type	Make and Interrupt Rating			Duty Cycle Rating		
IC4482CTTA104 100A - DPDT	Make	900 Amps	12-84VDC	80 Amps	100%	Continuous
	Interrupt	900 Amps	12-84VDC	100 Amps	50%	20 Minutes
IC4482CTTA100 100A - SPNO	Make	900 Amps	12-84VDC	400 Amps	5%	30 Seconds
	Interrupt	900 Amps	12-84VDC	600 Amps	2%	5 Seconds

150 Amp Contactors





Rating / Type	Make and Interrupt Rating			Duty Cycle Rating		
IC4482CTTA154 150A - DPDT	Make	1500 Amps	12-84VDC	100 Amps	100%	Continuous
	Interrupt	1500 Amps	12-48VDC	150 Amps	50%	20 Minutes
	Interrupt	1100 Amps	72-84VDC	600 Amps	5%	30 Seconds
IC4482CTTA150 150A - SPNO	Make	1500 Amps	12-84VDC	900 Amps	2%	5 Seconds
	Interrupt	1500 Amps	12-48VDC			
	Interrupt	1200 Amps	72-84VDC			
IC4482CTTA158 150A - DPDT (HD Tips)	Make	1500 Amps	12-84VDC			
	Interrupt	1500 Amps	12-48VDC			
	Interrupt	1100 Amps	72-84VDC			
IC4482CTTA168 150A - SPDT (HD Tips)	Make	1500 Amps	12-84VDC			
	Interrupt	1500 Amps	12-48VDC			
	Interrupt	1100 Amps	72-84VDC			

300 Amp Contactors


Rating / Type	Make and Interrupt Rating			Duty Cycle Rating		
IC4482CTTA304 300A - DPDT	Make	2000 Amps	12-84VDC	225 Amps	100%	Continuous
	Interrupt	2000 Amps	12-48VDC	300 Amps	50%	20 Minutes
	Interrupt	1500 Amps	72-84VDC	1200 Amps	5%	30 Seconds
IC4482CTTA300 300A - SPNO	Make	2000 Amps	12-84VDC	1800 Amps	2%	5 Seconds
	Interrupt	1500 Amps	12-48VDC			
	Interrupt	1500 Amps	72-84VDC			
IC4482CTTA368 300A - SPDT (HD Tips)	Make	2000 Amps	12-84VDC			
	Interrupt	2000 Amps	12-48VDC			
	Interrupt	1500 Amps	72-84VDC			

400 Amp Contactors

Rating / Type	Make and Interrupt Rating			Duty Cycle Rating		
IC4482CTTA400 400A - SPNO	Make	2000 Amps	12-84VDC	250 Amps	100%	Continuous
	Interrupt	2000 Amps	12-48VDC	400 Amps	50%	15 Minutes
	Interrupt	1500 Amps	72-84VDC	1300 Amps	5%	30 Seconds
(Note: 400 Amp uses Tin Oxide & Silver Tips)				1900 Amps	2%	5 Seconds

Typical Power Terminal Forms		Coil Number	Volts	Duty	100A	Coil Burden 150/300/400A
	SPNO	112	12 VDC	Int.	4.9A	5.8A
		118	18VDC	Int.	3.1A	3.6A
	SPDT	124	24 VDC	Int./Cont.	1.7A	1.9A
		136	36 VDC	Int.	1.0A	1.8A
	DPDT with interconnect bus	142	36 VDC	Cont.	0.8A	1.1A
		142	48 VDC	Int.	1.1A	1.4A
	DPDT	160	60 VDC	Int.	NA	0.8A
		176	72/80 VDC	Int.	0.6A	0.6A
		176	72 VDC	Cont.	0.5A	0.6A
		212	12 VDC	Cont.	3.3A	3.7A
		218	18 VDC	Cont.	2.0A	2.4A
		224	24 VDC	Cont.	1.0A	NA
		248	48 VDC	Cont.	0.8A	0.8A
		280	80 VDC	Cont.	---	0.5A
		324	24 VDC	Cont.	---	1.9A

Outline (For Reference Only)



Ordering Information

IC4482CTTA154	FR	124	X	N
Type	Terminal Form	Coil Number	Interlock	Arc Shields
See Table	See Table	See Table	X - None A - 2NO/2NC	N - None S - Yes

Note: Contact FSIP for replacement parts or if other contactor power terminal forms and/or voltages are required for your application.